

Mobi-mat® - AFX

Mobility & accessibility mat















has the label "Origine France garantie"!

Guaranteed France Origin is the unique certification attesting the French origin of a product.



- Anticorrosion
- > Permeable
- > Customizable
- > 100% recyclable
- > UV, weather & salt spray resistance
- Flexible
- > Lightweight

Retains

dust

sand and

> Robust



Dimension		Roll		Blue	Golden Sand
Width	Length	weight	diameter	Jay	Golden Sand
1m 3.25ft	5 m 16 ft	8 kg 18lb	30 cm 12"	300248-0500	300252-0500
	10 m 33 ft	15 kg 33 lb	35 cm 14"	300249-1000	300253-1000
	15 m 50 ft	21 kg 46 lb	43 cm 17"	300249-1520	300253-1520
	20 m 65 ft	28 kg 62 lb	50 cm 20"	300250-2000	300254-2000
	25 m 82 ft	34 kg 75 lb	56 cm 22"	300250-2500	300254-2500
	30 m 98 ft	41 kg 90lb	58 cm 23"	300251-3040	300255-3040
1,50m 5ft	5 m 16 ft	11 kg 24 lb	30 cm 12"	300256-0500	300260-0500
	10 m 33 ft	21 kg 46 lb	35 cm 14"	300257-1000	300261-1000
	15 m 50 ft	31kg 68 lb	43 cm 17"	300257-1520	300261-1520
	20 m 65 ft	41 kg 90 lb	50 cm 20"	300258-2000	300262-2000
	25 m 82 ft	50 kg 110 lb	56 cm 22"	300258-2500	300262-2500
	30 m 98 ft	60 kg 132 lb	58 cm 23"	300259-3040	300263-3040
2m 6.5ft	5 m 16 ft	15 kg 33 lb	30 cm 12"	300264-0500	300268-0500
	10 m 33 ft	28 kg 62 lb	35 cm 14"	300265-1000	300269-1000
	15 m 50 ft	41 kg 90 lb	43 cm 17"	300265-1520	300269-1520
	20 m 65 ft	54 kg 119 lb	50 cm 20"	300266-2000	300270-2000
	25 m 82 ft	67 kg 148 lb	56 cm 22"	300266-2500	300270-2500
	30 m 98 ft	80 kg 176 lb	58 cm 23"	300267-3040	300271-3040
3m 10ft	3 m 10 ft	12kg 26 lb	25cm 8"	-	300276-0306
	5 m 16 ft	22 kg 49 lb	30 cm 12"	-	300276-0500
	10m 33 ft	42 kg 93 lb	35 cm 14"	-	300277-1000
	15 m 50 ft	61 kg 134 lb	43 cm 17"	-	300277-1520
	20 m 82 ft	81 kg 179 lb	50 cm 20"	-	300278-2000
	25 m 98 ft	100 kg 220 lb	56 cm 22"	-	300278-2500

Exact widths in m \rightarrow 0,99m | 1,53m | 1,98m | 3,06m

Mobi-mat® AFX can support vehicle of 3.5 tons & more

(depending on the type of soil)

Tensile strength*	>100 kN/m 10 t/m 680lb/ft
Weight	<2kg/m² 4.4lb/sqft
Temperature of use & storage*	-40°C / + 80°C -104°F / +176°F

*Non-contractual technical data which does not constitute any guarantee



Company certified ISO 9001 and ISO 14001



Up to 5 years warranty



Lifespan 10 years and more



Mobility: maximum ground grip



Bare foot

> Soft

> Not burn feet



Compliance

Disable standards



Pedestrians with

> Strollers





Compatible with vehicle crossing

- Bikes
- Quads, Scooters...
- Cleaning and service vehicles



Light strip option - USB power cable Maximum power 5W



Quick installation & low maintenance

QUICK INSTALLATION

Mobi-mat® is easy and quick to install. Put, unroll and anchor the mat on the ground!

Several types of anchors are possible in option:

- Concrete anchor
- Wood anchor
- Hard bottom anchor
- Underwater anchoring on soft bottom
- Underwater anchoring on hard bottom

LOW MAINTENANCE

Excellent corrosion resistance:

- Galvanized steel anchors
- Aluminum rivets and stainless steel eyelets

Use a broom, leaf blower or high pressure water jet to clean Mobi-mat®.









All anchors are provided with the mat. Depending on your mats' dimensions, the number of eyelets and anchors will be different



Multiple applications

BEACHES & BOATRAMPS



PARKS & **G**ARDENS



TOURISM





CONSTRUCTION & LANDSCAPING



EVENTS







SKI STATIONS



FARMING



What are our complementary products?







DESCHAMPS MATS SYSTEMS

218 Little Falls Road, Unit 12 Cedar Grove NJ 07009 – USA +1 973 928 3040 GSA contract #: GS-07F-0316L

