



Lightweight & robust surface
easy to install

Patented surface enabling vehicles to cross all types of slippery soils: grass, sand, gravel or mud.



Mobi-vehicle™ has the label "Origine France Garantie"!



Guaranteed France Origin is the unique certification attesting the French origin of a product.

ADVANTAGES



- > Anti-corrosion
- > Permeable
- > Rot-proof
- > 100% recyclable
- > UV & weather resistant
- > Customizable
- > Flexible
- > Lightweight
- > Robust
- > Retains dust

Technical specificities

Mobi-vehicle™ A2X can support up to 40 tons (depending on the type of soil)

Dimensions		Roll weight	Roll diameter	Brown eagle	Golden sand	White
Width	Length					
1m 3.25ft	5m 16ft	10kg 22lb	40cm 16"	-	300340-0500	-
	10m 33ft	18kg 40lb	50cm 20"	-	300341-1000	-
	15m 50ft	26kg 57lb	55cm 22"	-	300341-1520	-
	20m 65ft	35kg 77lb	60cm 24"	-	300342-2000	-
	25m 82ft	43kg 95lb	65cm 26"	-	300342-2500	-
1,50m 5ft	5m 16ft	14kg 31lb	40cm 16"	300328-0500	-	-
	10m 33ft	26kg 57lb	50cm 20"	300329-1000	-	-
	15m 50ft	39kg 86lb	55cm 22"	300329-1520	-	-
	20m 65ft	51kg 112lb	60cm 24"	300330-2000	-	-
	25m 82ft	63kg 139lb	65cm 26"	300330-2500	-	-
2m 6.5ft	5m 16ft	19kg 42lb	40cm 16"	-	300348-0500	-
	10m 33ft	35kg 77lb	50cm 20"	-	300349-1000	-
	15m 50ft	52kg 115lb	55cm 22"	-	300349-1520	-
	20m 65ft	68kg 150lb	60cm 24"	-	300350-2000	-
	25m 82ft	85kg 187lb	65cm 26"	-	300350-2500	-
3m 10ft	5m 16ft	27kg 60lb	40cm 16"	-	300352-0500	-
	10m 33ft	52kg 115lb	50cm 20"	-	300353-1000	-
	15m 50ft	77kg 170lb	55cm 22"	-	300353-1520	-
	25m 82ft	126kg 278lb	65cm 26"	-	300354-2500	-
	4,20m 13.8ft	5m 16ft	38kg 84lb	40cm 16"	-	-
10m 33ft		72kg 159lb	60cm 24"	-	-	220468-1000
15m 50ft		107kg 236lb	65cm 26"	-	-	220468-1520

Exacts widths in m → 0,99m | 1,53m | 1,98m | 3,06m



Company certified ISO 9001 and ISO 14001



Light strip option
USB power cable
Maximum power 5W



Up to 5 years warranty



Lifespan 10 years and more



Mobility: maximum ground grip



Pedestrians

- > Safe pathway for pedestrians traffic



Traffic

- > Cars
- > Trucks
- > Construction equipments



- > **Technical surface** enabling traction to wheeled vehicles



- > **Preservation of soil condition**

Tensile strength*	>100 kN/m 10 t/m 680lb/ft
Weight	<2kg/m² 4.4lb/sqft
Temperature of use & storage*	-40°C / + 80°C -104°F / +176°F

*Non-contractual technical data which does not constitute any guarantee

Quick installation & low maintenance

QUICK INSTALLATION

Mobi-vehicle™ is easy and quick to install.

Put, unroll and anchor the mat on the ground !

Several types of anchors are possible in option:

- **Concrete anchor**
- **Wood anchor**
- **Hard bottom anchor**
- **Underwater anchoring on soft bottom**
- **Underwater anchoring on hard bottom**

EASY MAINTENANCE

Excellent corrosion resistance:

- **Galvanized steel anchors**
- **Aluminum rivets and stainless steel eyelets**

Use a broom, leaf blower or high pressure water jet to clean Mobi-vehicle™.



*All anchors are provided with the mat.
Depending on your mats' dimensions, the number of eyelets and anchors will be different.*

Multiple applications

CONSTRUCTION



LANDSCAPING



PARKS & GARDENS



What are our complementary products?

Mobi-mat® Accessibility mat AFX



Mobi-roller™ Mat dispenser



Mobi-deck™ Rigid panel



Mobi-fence™ Sand & Dust fence

