

Mobi-vehicle™- MM3V25







Mobility & accessibility mat



Patented surface



Mobi-vehicle™ has the label "Origine France Garantie"!

Guaranteed France Origin is the unique certification attesting the French origin of a product.


- > Retains dust
- > Grip improvement on soil up to 20%
- Robust

ADVANTAGES

- Flexible
- Anti-erosion
- > Permeable
- > Rot-proof
- > 100% recyclable
- > UV & weather resistant
- Customizable

Technical specifications

Dimension			Reference
Width	Lenght	Weight White	White
1,05m 3.5ft	5m 16ft	42kg 93lb	220496-0500
2,1m 6.9ft	5m 16ft	83kg 185lb	220497-0500
4,2m 13.8ft	5m 16ft	170kg 375lb	220498-0500
4,2m 13.8ft	10m 33ft	340kg 750lb	220498-1000



Mobi-vehicle™ MM3V25 can support up to 80 tons (depending on the type of soil)

Tensile strength*	> 100 kN/m 10 t/m 680lb/ft	
Weight	10 kg/m² 22lb/sqft	
Temperature of use & storage*	-40°C / + 80°C -104°F / +176°F	

*Non-contractual technical data which does not constitute any guarantee



Up to 5 years warranty



Lifespan 10 years and more





Mobility: high grip & lift on the ground



Traffic

- Cars
- Trucks
- > Construction equipments



> Technical surface enabling traction to wheeled vehicles



Preservation of soil condition



Quick installation & low maintenance

QUICK INSTALLATION

Mobi-vehicle™ is easy and quick to install. Put, unroll and anchor the mat on the ground!

Depending on your mats' dimensions, the number of eyelets and anchors will be different:

- Stakes of 500mm included (standard)
- Stakes of 1000mm in option
- Earth anchors in option

EASY **M**AINTENANCE

Excellent corrosion resistance:

- Galvanized steel anchors
- Aluminum rivets and stainless steel eyelets

Use a broom, leaf blower or high pressure water jet to clean Mobi-vehicle™.







Anchors included



Multiple applications

CONSTRUCTION & BUILDING SITES























